DART SERVICE INSTRUCTION TO AMEND INSTALLATION INSTRUCTIONS IIN-D139-799 REV. I AND

TO AMEND INSTALLATION INSTRUCTIONS IIN-D139-799 REV. I AND INSTRUCTIONS FOR CONTINUED AIRWORTHINESS ICA-D139-799 REV. 8 OR LATER APPROVED REVISION REF. FAA STC: SR02138SE

REF. EASA STC: 10038656

1.0 PURPOSE

The purpose of this Service Instruction is to address customer concerns with leaking water around the D2586 Latch as part of the D139-799-013 Cargo Door Hinge Kit when installed on the Agusta AB/AW139 model aircraft.

2.0 INSTALLATION

- 2.1 Remove the MS27039-1-17 Screw, NAS1149D0363J Washer, MS21042L3 Nut, D2585 Mounting Channel, D2621 Latch Plate per Figure 1. Retain D2585 Mounting Channel and D2621 Latch Plate. Remove the D2586 Latch.
- 2.2 Install the D5275-041 Door Latch Assy in existing mounting hole using hardware shown in Figure 1. Torque MS21042L3 Nut 15-25 in-lb. Adjust screw to ensure compression of door seal and lock in position with nut.




Figure 1 - Door Latch Installation and Removal

| Α | NEW IS | SSUE VS | | | 15.06.15 |
|---------------|--------|----------------|--|--|--------------|
| REV. | | DESCRIPTION BY | | | DATE |
| DESIGN | | VS | DART AEROSPACE USA, INC. | | |
| DRAWN | | VS | | | |
| CHECKED | | HS | DRAWING NO. DSI 9727 | | REV. A |
| MFG. APPR. | | N/A | | | SHEET 1 OF 2 |
| APPROVED | | НŞ | TITLE | | SCALE |
| DE APF | PR. | # | SEALED LATCH | | NTS |
| DATE 15.06.15 | | | COPYRIGHT © 2015 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND COMPIDENTIAN DIS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COMPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC. | | |

3.0 MAINTENANCE

Maintain D5275-041 Latch Assy per the instructions provided in ICA-D139-799 for the D2586 Latch.

4.0 WEIGHT AND BALANCE

This change has negligible effect on Weight and Balance.

5.0 PARTS LIST

| QTY -011 | PART NUMBER | DESCRIPTION ALTERNATE LATCH | | |
|-------------|---------------|-----------------------------|--|--|
| Х | DSI 9727-011 | | | |
| | | | | |
| 1 | D5275-041 | DOOR LATCH ASSY | | |
| 1 | MS27039-1-17 | SCREW | | |
| 1 | NAS1149D0363J | WASHER | | |
| 1 | MS21042L3 | NUT | | |

| Α | NEWIS | SSUE | | | 15.06.15 | |
|---------------|-------|-------------|---|--|--------------|--|
| REV. | | DESCRIPTION | | | DATE | |
| DESIGN | | VS | DART AEROSPACE USA, INC. | | INC | |
| DRAWN | | VS | KENT, WA | | | |
| CHECKED | | HS | DRAWING NO. | | REV. A | |
| MFG. APPR. | | N/A | DSI 9727 | | SHEET 2 OF 2 | |
| APPRO | VED | HŞA | TITLE | | SCALE | |
| DE APPR. | | -HH | SEALED LATCH | | NTS | |
| DATE 15.06.15 | | | COPYRIGHT © 2015 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT | | | |